




SPECIAL MONOLITHIC COMBINATION CURB AND GUTTER

- 3 FT. TO 6 FT. GUTTER PAN ; 8" DEPTH
- 3 FT. TO 6 FT. GUTTER PAN ; 9" DEPTH
- 3 FT. TO 6 FT. GUTTER PAN ; 10" DEPTH

NOTES:

1. JOINT SPACING FOR COMBINATION CURB & GUTTER IS 10 FEET
2. SEE SPECIFICATIONS FOR LOCATION AND DESCRIPTION OF TREATMENT FOR THE TYPES OF JOINTS USED.
3. UNLESS OTHERWISE SPECIFIED A LONGITUDINAL TIE DEVICE PLACED AT MIDDLE OF KEYWAY (NOT SHOWN), SHALL BE USED AT CONSTRUCTION JOINT BETWEEN COMBINATION CURB & GUTTER AND RIGID PAVEMENT. SEE BC 572.61-1.

	APPROVED :  DIVISION CHIEF, TRANSPORTATION ENGINEERING AND CONSTRUCTION  DIRECTOR, DEPARTMENT OF TRANSPORTATION	CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION TRANSPORTATION ENGINEERING AND CONSTRUCTION	ISSUED 8 / 2010	REVISED 	REVISED
	SPECIAL MONOLITHIC COMB. CURB & GUTTER			STANDARD NO. BC 620.12	
				SCALE : NONE	SHEET 1 OF 1