




DIAGONAL BAR DETAILS

NOTES

1. APPLICABLE TO SLIP FORM CONSTRUCTION METHOD ONLY.
2. FOR BARRIER TYPES 1 AND 2 BARRIERS CONSTRUCTED ON EXISTING RIGID PAVEMENT.
3. DIAGONAL NO. 4 BARS SHALL BE ASTM A615 GRADE 60.
4. ALL REINFORCEMENT BARS INCLUDING ENDS AND TIES SHALL BE EPOXY COATED.
5. REFER TO STANDARDS FOR SPACING OF VERTICAL AND HORIZONTAL REINFORCEMENT.

	APPROVED:  DIVISION CHIEF, TRANSPORTATION ENGINEERING AND CONSTRUCTION	CITY OF BALTIMORE DEPARTMENT OF TRANSPORTATION TRANSPORTATION ENGINEERING AND CONSTRUCTION	ISSUED	REVISED	REVISED	
	 DIRECTOR, DEPARTMENT OF TRANSPORTATION		DIAGONAL BAR FOR SLIP FORMED 34 " OR 42 " F SHAPE SINGLE FACE CONCRETE TRAFFIC BARRIER	8 / 2010		
			STANDARD NO. BC 648.07	SCALE : NONE	SHEET 1 OF 1	