



**GENERAL NOTES**

1. MINIMUM LENGTH OF RAIL TUBE TO BE 18'-0" NOMINAL
2. RAIL ALIGNMENT TO BE STRAIGHT AT SPLICES NO LATERAL BEND PERMITTED WITHIN THE SPLICES THIS DOES NOT PRECLUDE THE SHOP FABRICATION OF BENT SPLICES.
3. BOX BEAMS FOR CURVED MEDIAN BARRIERS FOR CURVES GREATER THAN 3°-15' SHALL BE SHOP WORKED TO THE REQUIRED CURVATURE.

NOTE:  
FOR DETAILS NOT SHOWN  
SEE STD. NOS.  
BC 662.01-1 & BC 662.01-2  
BC 662.02-1 & BC 662.02-2  
BC 662.51-1 & BC 662.51-2



APPROVED:  
*Frank Murphy*  
DEPUTY DIRECTOR - OPERATIONS  
*Khalil Zane*  
DIRECTOR, DEPARTMENT OF TRANSPORTATION

CITY OF BALTIMORE  
DEPARTMENT OF TRANSPORTATION  
TRAFFIC DIVISION  
**TRAFFIC BARRIER BOX BEAM  
MEDIAN BARRIER  
TYPICAL END TREATMENT**

ISSUED	REVISED	REVISED
8 / 2010		
STANDARD NO. BC 662.61-2		
SCALE: NONE	SHEET 2 OF 2	